


Features

- Plastic clamp designed for pipe fixing.
- Fast installation. This clamp can be tightly closed by pressing the pipe without tools.
- Developed for direct impact fixing with a nailer. Compatible with FORCE ONE+, FOX and other nailers.
- Can be fixed with 4.5 mm diameter screws in a 6 mm plug.
- Alignment mark. Two marks on the base make it easy to align the shots.
- Smart design with side tabs to join multiple clamps that saves fixings points.

Certificates and approvals

ETA · CE · ICC ES · HALOGEN FREE · RoHs COMPLIANT · MADE IN GERMANY

Main dimensions



Reference	Ø [mm]	L [mm]	H [mm]	B [mm]
916UT	15.5	23	25.5	16
920UT	19.5	25	29.5	16
925UT	24.5	30.5	34	16
932UT	31	38	42	16
940UT	39	46	50	16

Base material

- Steel
- Concrete
- Concrete block
- Solid brick

Installation procedure





Product specifications

- Material: HDPE 5502
- Available in grey (RAL 7035)
- Temperature:
  - Installation: 0 ºC / +45 ºC
  - Continuous use: -20 ºC / +100 ºC
  - Spikes -30 ºC / +120 ºC
- Resistance: 6 - 10 kg according to size(*)

(*) Clamp breaking strength is lower than the nail resistance value

Installation parameters

Material		Concrete	Concrete block	Steel
Minimum distance between anchors	s_{min} (mm)	40	40	40
Minimum edge distance	c_{min} (mm)	75	100	25
Minimum thickness	h_{min} (mm)	100	35	3.5

This document is intellectual property of CELO FIXINGS. Copy is forbidden and will be prosecuted.
Copy, total or partial, must have the written agreement of CELO FIXINGS. F.204 v.01- Technical Data Sheet

Range of pipes

Reference	Diameter	
	Metric [mm]	Plastic [mm]
916UT	16	16
920UT	20	20
925UT	25	25
932UT	32	32
940UT	40	40

This document is intellectual property of CELOFIXINGS. Copy is forbidden and will be prosecuted.
Copy, total or partial, must have the written agreement of CELOFIXINGS. F.204 v.01- Technical Data Sheet